



Design to the next level.

thelift+ SERIES A

thelift+ challenges the elevator market by delivering tailor-made platform lifts with a clear focus on design and comfort. We target the quality-conscious who are interested in technological design and comfort, at an attractive pricing.

Choose from flexible solutions regarding size, color, options and glass system. thelift+ is designed in a modern and discreet Scandinavian design language that fit into most environments. thelift+ can be ordered with a unique glass system that gives an exclusive impression.

- **Glass system:** Unique solution of jointing glass sections
- **A stable platform:** Extra stable construction for the safest and best comfort
- **Low noise level:** Encapsulated drive package that provides low noise level when in operation: only 30dB
- **Soft-close doors:** Damping systems on doors that provide soft and silent door closures
- **EMC:** thelift+ has undergone a complete laboratory and tested regarding electromagnetic compatibility (EMC)

Read more at www.thelift.se



thelift+

thelift Elevators Sweden AB
E-mail: info@thelift.se
www.thelift.se





COLORS


Available in any color from RAL Color Chart
K7 Classic Chart - Powder coating technology

GLASS WALLS


10,76 mm laminated security glass



Clear glass



Toned glass




Dark glass

DOORS


All doors have soft-close as standard, which enables soft and silent door closures

FLOORS


Flexible floor options that fit adjacent floors



Light Oak



Dark Oak



Bolon




Coin Black

PLATFORM SIZES

This is a selection of our standard models

A14-10


1515



Size: 1000 x 1467 mm
Rated load: 500 kg

A14-11


1515



Size: 1100 x 1467 mm
Rated load: 500 kg

A13-10


1415



Size: 1000 x 1367 mm
Rated load: 500 kg

A13-11

1415



Size: 1100 x 1367 mm
Rated load: 500 kg

DRIVE SYSTEM

2.2 kW electric motor

WARRANTY

24 month warranty



INSTALLATION

Short installation time.
50 mm under floor level,
alternatively direct on
floor with ramp



COMPLIES WITH

European machinery
directive, 2006 / 42 / EC

European Standard
EN 81-41

Battery-powered
emergency lowering

OPERATING HEIGHT

250-14000 mm

TRAVEL HEIGHT

2 to 6 floors



CONTROL PANEL

Constant pressure control
(press & hold) in the EU

Impulse control
(press once) outside the EU



SPEED

Max 0,15 m/s
in the EU

Max 0,25 m/s
outside the EU

POWER SUPPLY

1 x 230 V
3 x 230 V
3 x 400 V